

NEW

twenty[®]26



Delivering greater dynamics, resolution and higher levels of musicality



The pinnacle of the legendary **twenty[®]** series, the **twenty.26**, features the same traits as its siblings - finesse, delicacy and musicality - but with an added ability to convey huge dynamic impact and the sheer scale of a musical performance, it can engulf the largest room. This exceptional, well thought out design will excel with a vast array of amplification due to its ease of drive and well-tempered balance, and its transparency ensures that users improving other elements of their signal path will appreciate the full benefit of their upgrades. This is a model that takes every musical style in its stride and delivers the greatest level of overall clarity of any of the **twenty[®]** series, or indeed of any speaker in this class.

Amarone

Specific features of the **twenty**®26

The critical mid-range

PMC is world renowned in both the professional and HiFi realms for superlative soft dome mid-range drivers. The development of the newly designed **twenty** series mid-range sets the **twenty**26 apart from any other model in its class. It provides astounding transparency - vocals are projected into the room with all their emotion and individual character.



Articulate, deeper bass

To deliver the extraordinary bass depth with detail requires large, well controlled cone excursions, and the custom-made **twenty**26 low frequency unit takes these in its stride. Coupled with **ATL**™ loading, every plucked bass and kick drum is unquestionably lifelike.




To seamlessly integrate the high, mid and bass drivers of the **twenty**26 takes a highly complex and well-engineered crossover. It ensures the perfect supply of frequencies for each of the three drive units.



Specification

Freq response	27Hz – 25kHz
Sensitivity	86dB 1W 1m
Recommended amp power	50 - 300W
Effective ATL™	3.3m 11ft
Impedance	8 Ohm
Drive units	LF PMC twenty ® series, lightweight doped 7"/177mm cone with cast alloy chassis MF PMC 50mm twenty ® series dome mid-range HF PMC/SEAS®, 27mm twenty ® series, SONOLEX™ Soft dome, Ferrofluid cooled
Crossover freqs	380Hz & 3.8kHz
Input connectors	3 pairs 4mm sockets (Tri-amp or Tri-wire)
Dimensions	H 1062mm 41.8" (+25mm spikes) W 190mm 7.5" D 439mm 17.3" (+16mm grille)
Weight	22.5kg 49 lbs
Finishes	Oak, Walnut, Amarone & Diamond black (high gloss)



Each of the three precision drivers can be fed individually via the British engineered terminals